

February 21, 2012

Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, CR 2120, Texas 75713, Phone 903.534.8021 • Fax 903.581.4376

Product Data Sheet



NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

SYNTHETIC REFRIGERATION LUBRICANTS

PGI SERIES

Summit PGI synthetic lubricants were designed for use in the compression of propane in refrigeration or unloading service. Available in three grades for rotary screw and reciprocating compressors, PGI is especially suitable for wet gas situations. Due to the varying make-up of gases and operating temperatures, please contact your Summit representative for specific product recommendations.

Physical Properties

PRODUCTS	PGI-68	PGI-100	PGI-150
Viscosity Grade	68	100	150
Viscosity			
@ 40°C, cSt	69	102	156
@ 100°C, cSt	12.7	18.0	26.2
@ 100°F, SUS	349	519	788
@ 210°F, SUS	70.2	92.2	128.1
Viscosity Index	186	195	205
Pour Point, °F (°C)	-54(-48)	-49(-45)	-44(-42)
Flash Point, °F (°C)	480(249)	485(252)	495(257)
Density,g/ml, 60°F	0.992	0.996	1.000
100°F	0.954	0.958	0.961

Shelf Life:

Product shelf life is 3 years from the date of manufacture, after which the product should be recertified prior to use.

Thermal Characteristics:

Specific Heat	Thermal Conductivity
Cal/g-°C	BTU/Hr/(Ft °F)
60°C = 0.48	100°F = 0.095
80°C = 0.49	200°F = 0.090
100°C = 0.51	